



IPC 2U-2306

The **IPC 2U-2306** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 2U-2306** offers the possibility to install six 2.5" or 3.5" Hot-Swap HDDs and two 5.25" external HDD. The **IPC 2U-2306** has four 80mm fans, which are mounted directly at the back of the drive brackets and ensure therefore a reliable and optimal cooling.

Specifications

Motherboard	Mini ITX, µATX, ATX, eATX, SSI EEB maximal motherboard size WxD: 305mm x 345mm, 12" x 13.5"
Drive Bays	6x 2.5" or 3.5" external Hot Swap (max. 6G) 2x 5.25" external hard drives
Front connectors	USB 2.0: 2
Cooling System	Internal: 4x 80mm (included, Molex connector)
Controls	Power-Button Rest-Button
LED	Power HDD Activity 3x Network Activity Alert
Power Supply	2HU Server Power Supply
Material	1.0/1.2mm Steel
Packing Units	Shipping Units: 1 piece Pallet: 21 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887116
EAN-Code	4260133126374
Scope of Delivery	Screw Set Mounting rails for 5.25" external hard drive Assembly tool Mounting brackets for 2HU PSU 4x 80mm fan included 7x perforated Low Profile slot brackets (rear) USB 2.0 as block connector Hot-Swap backplane with SFF-8087 socket*
Features	

* The backplane is only compatible with a SAS-Controller with S-ATA connectors.
In operation with SAS-Controllers, please order the optional Mini SAS SFF 8087 cable in right quantity.

Dimensions and Weight

	Cage	Case	Package
Height	89mm	89mm	155mm
Width	433mm	480mm	560mm
Depth	650mm	690mm	830mm

Weight (net): 9.74 kg
Weight (gross): 12.02 kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Without

Certification:

