



IPC 3U-30248

The **IPC 3U-30248** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 3U-30248** provides the possibility to remove the two HDD cages on both sides and therefore to mount up to six 5.25" external hard drives. In the middle four external 3.5" HDDs are also available.

One 120mm and two 60mm fans guarantee an optimal cooling.

Additional extras like easily reachable [USB 3.0](#) and USB 2.0 connectors and the lid with the snap locks complete this total package.

Specifications

Motherboard	Mini ITX, mATX, μ ATX, ATX, eATX, SSI CEB maximal motherboard size WxD: 305mm x 270mm, 12" x 10.6"
Drive Bays	5.25" external: 6* 3.5" internal: 12* 2.5" internal: 14*
Front Connectors	USB 3.0: 1 USB 2.0: 1
Cooling System	Front: 1x 120mm (included, Molex connector) 5.25" drive front bezel: 6x 40mm (optional) Rear: 2x 60mm (included, 3pin connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity Alert
Power Supply	ATX PSU
Material	1.0/1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 18 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887107
EAN-Code	4260133126282
Scope of Delivery	Screw Set Mounting rails for 3.5" hard drives
Features	HDD cages removable and optional positionable Only 5 slot openings + 1 slot with optional Riser Card 1x 120mm and 2x 60mm fan included USB 3.0 and USB 2.0 as block connector Lid with snap lock

*can vary by using several mounting options

Dimensions and Weight

	Cage	Case	Package
Height	133.5mm	133.5mm	200mm
Width	433mm	480mm	560mm
Depth	480mm	515mm	660mm

Weight (net): 9.48Kg
Weight (gross): 11.75kg

Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Without

Certification:

