Inter-Tech Elektronik Handels GmbH

IPC 2098-SL



19" IPC 2098-SL 2U - Classic 19" Rack with a lot of space for different drives

You can remove the HDD cages with a few steps for easy mounting of internal devices.

On top you can mount an ATX PSU to get a cost-efficient and professional solution.

Alternatively you can mount a 2U PSU.

The lockable doors in front of the slots prevent, unauthorized access.

Integrated air filters ensure clean air and a flawless cooling.



IPC 2098-SL

Specifications	
Motherboard	Mini ITX, mATX, μATX, ATX maximal motherboard size WxD: 305mm x 290mm, 12" x 11.4"
Max. Drive Bays	5.25" external: 1 3.5" external: 1* 3.5" internal: 5* 2.5" internal: 3*
Front Connectors	USB 2.0: 2
Cooling System	Front: 2x 60mm (optional) Inside: 4x 80mm (3x included, Molex connector, 1x optional)
Controls	Power-Button Reset-Button
LED	Power HDD Activity
Power Supply	ATX / 2HU PSU
Material	1.0-1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 20 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number EAN-Code	88887127 4260133128071
Scope of Delivery	Keys Screw Set
Features	Air filter

Dimensions and Weight

	Cage	Case	Package
Height	87mm	89mm	175mm
Width	427mm	485mm	545mm
Depth	565mm	615mm	720mm
eiaht (net):	8.72 kas		

ower Supply	L	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4.
P8 12V 8Pin	-	_ 4
PCI-Express 6+2Pin	1100	IJĻ
PCI-Express Con	4h0	
IDE 4Pin	thr	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Removable HDD cages

Lockable front doors

(backside)

4x screwed Low Profile brackets

USB 2.0 internal as block connector *can vary by using several mounting options

Certification:

Weight (gross): 10.8 kgs