

## IPC 4088-S



# 19" IPC 4088-S 4U - Classic 19" Rack with a lot of space for different drives

You can remove the HDD cages with a few steps for easy mounting of internal devices.

You can mount 4  $\times$  2.5" Hard drives on a crossbeam inside the case. The crossbeam is also equipped with a slot card holder to ensure a safe usage.

The lockable doors in front of the slots prevent, unauthorized access.



### IPC 4088-S

#### **Specifications**

Motherboard

maximal motherboard size WxD: 305mm x 270mm, 12" x 10.6"

Max. Drive Bays

5.25" external: 3/2¹
3.5" external: 0/1¹
3.5" internal: 8
2.5" internal: 5\*

Front Connectors

USB 2.0: 2

Cooling System

Cooling System

Front: 1x 120mm

(serial, Molex Connector)

Rear: 2x 80mm

Rear: 2x 80mm (optional)

Mini ITX, mATX, µATX, ATX

Controls Power-Button Reset-Button

LED Power
HDD Activity

Power Supply ATX PSU, PS2 Mini-Redundant
Material 1.0-1.2mm Steel

Packing Units Shipping Unit: 1 Piece
Pallet: 20 Pieces

Guarantee and WarrantyCase 24 Months WarrantyArticle Number88887178EAN-Code4260133128101

Scope of Delivery Keys
Screw Set

Mounting frame 5.25" to 3.5" external

Features Removable HDD cages

7x screwed and perforated brackets

Slot Card holder each 1x for short, mid and high Slot Cards

Lockable front door

USB 2.0 internal as block connector

\*max height 4x 9,5mm and 1x 15mm  $^{\rm 1}$  by Using the mounting frame 5.25" to 3.5" external, one 5,25" is dropped

#### **Dimensions and Weight**

	Cage	Case	Package
Height	175mm	178mm	270mm
Width	427mm	485mm	550mm
Depth	448mm	483mm	590mm

Weight (net): 10.0 kgs Weight (gross): 12.1 kgs

### Power Supply

	Connector	Quantity	Max. Length
	Mainboard 20+4Pin	-	-
	P4 12V 4Pin	-	-
	P4/EPS 4+4Pin	-	4.
	P8 12V 8Pin	-	
	PCI-Express 6+2Pin		
	PCI-Express in		
	IDE 4Pin		-
	S-ATA	-	-
	Floppy	-	-
	RPM sensor cable	-	-
	Fan Control	-	-
	Fan: 120mm	-	-

Certification:

