



The **KVM KS-3104** is a professional 4-Port KVM-Switch. The **KVM KS-3104** is usually used in server racks to switch and manage several installed servers with just one mouse, keyboard and monitor.

The in-build password protection prevents unauthorized access.

The KVM will be connected to your Computers with a RJ45 cable (usually LAN cables, Cat.5e or higher, max. 60m) and with the 4 included Dongle to VGA and USB.

## Specifications

Keyboard / Mouse Connection	USB/PS2
Monitor Connection	DB15 VGA
Slot for IP-Expansion modul	1
Outputs	4
Maximal manageable PCs	256 max. 2 levels
Suitable for Server Racks	Min. 400mm depth
Connectors	4x RJ45, RJ45 Dongle (VGA/USB, Keyboard, Mouse)
LEDs	4x connect, 4x selection
Supported operating system	No Restrictions
Max. Transfer Length	60m
Switch Modi	Hotkey OSD Menu
Switch Scan-Time	1-255s (OSD chooseable)
DDC	•
Display Resolution	1920x1080
Display Frequency	75Hz
Power	External PSU
Input	9V / 1A
Material	Rust-resistant Steel
Operating Temperature	-10°C~60°C
Storage Temperature	-30°C~70°C
Humidity	0-80%
MBTF	approx. 120000h
Netto-Dimensions (H/W/D)	43x432x156mm
Package-Dimensions (H/W/D)	150x465x200mm
Weight net.	1,98Kgs
Weight gros.	3,17Kgs
Packing units	Shipping unit: 1 piece
Guarantee and Warranty	24 Month Warranty
Article number	88887163
EAN-Code	4260133127883
Scope of Delivery	4x Dongle RJ45 auf VGA/USB (20/40 cm) 19" installation angle External PSU (Input: 100-240V / 0,35A Output: 9V / 1A) User manual on CD (English/German)
Features	4x Hotkeys Password protection for Keyboard and Monitor
Optional Equipment	KVM IP-Modul KI-3101 (Art. 88887172)

• = existent  
- = nonexistent