



IPC 2U-2129N

The **IPC 2U-2129N** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 2U-2129N** provides the possibility to mount a 1U or 2U server power supply at the rear of the chassis as well as a normal ATX power supply with 80mm fan in the front.

Furthermore the **IPC 2U-2129N** is equipped with four 80mm fans and perforated slot brackets for excellent cooling.

Both serial USB front connectors, one of them **USB 3.0**, round off the whole package.

Specifications

Motherboard	Mini ITX, mATX, µATX, ATX, eATX, SSI EEB maximum motherboard size WxD: 305mm x 350mm, 12" x 13.8"
Drive Bays	5.25" external: 2 3.5" external: 6 3.5" internal: 6
Front Connectors	USB 3.0: 1 USB 2.0: 1
Cooling System	Internal: 4x 80mm (assembled board 4x 3Pin to 1x Molex) Rear: 1x 60mm (optional, not possible when using 2U/1U PSU)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity 1x Alert
Power Supply	1U/2U Server PSU ATX PSU with 80mm fan
Material	1.0-1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 18 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887194
EAN-Code	4260133128385
Scope of Delivery	Screw Set Mounting frame for 2U / 1U PSU
Features	Serial 4x 80mm fan Possibility to mount a 1U/2U server PSU in the rear or a ATX PSU with 80mm fan in the front Removable and optional positionable HDD-cages 5.25" drives screwless mountable Slot brackets screwed and perforated (Riser Slot rear wall optional (Item no. 88887160))

Dimensions and Weight

	Cage	Case	Package
Height	89mm	89mm	155mm
Width	432mm	482mm	565mm
Depth	650mm	680mm	825mm

Weight (net): 8.93Kgs
Weight (gross): 11.27Kgs

Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Without

Certification:

