



IPC 2U-2404L

The **IPC 2U-2404L** is the perfect rack for a low-priced storage system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 2U-2404L** offers the possibility to mount maximal four 2.5" or 3.5" Hot-Swap HDDs and one internal 2.5" or 3.5" HDD (by using a 2.5" with 9.5mm height also a 3.5" HDD simultaneously). The **IPC 2U-2404L** is equipped with three serial 40mm fans. At the rear of the chassis you can mount an ATX PSU with 80mm fan or a Mini-Redundant PS/2 PSU.

Both serial USB front connectors, one of them **USB 3.0**, round off the whole package.

Specifications

Motherboard	Mini-ITX, µATX max. motherboard size WxD: 244mm x 244mm, 9,6" x 9,6"
Drive Bays	2.5" or 3.5" Hot-Swap (max. 6G): 4 2.5" or 3.5" internal: 1 ¹
Front Connectors	USB 3.0: 1 USB 2.0: 1
Cooling System	Internal: 3x 40mm (serial, 3Pin with 4Pin connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity 1x Alert
Power Supply	ATX PSU with 80mm fan or Mini-Redundant PS/2
Material	1.0/1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 21 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887113
EAN-Code	4260133128644
Scope of Delivery	Screw Set Mounting frame for ATX PSU Mounting tool
Features	Serial 3x 40mm fans 4x perforated Low-Profile slot bracket (Rear) USB 3.0 and USB 2.0 internal as block connector Hot-Swap backplane with SFF 8087 socket (max. 6G) ² Mesh-Grid-Front with dust filter

¹simultaneously only if 2.5" drive with max. 9.5 mm height

² The backplane is only compatible with a SAS-Controller with SFF-8087 connector.

To use the backplane with a SATA-Controller, please order the optional SFF8087 cross-over cables (88885237) in right quantity

Dimensions and Weight

	Cage	Case	Package
Height	89mm	89mm	155mm
Width	433mm	480mm	550mm
Depth	480mm	520mm	660mm

Weight (net): 6.72 kgs

Weight (gross): 8.75 kgs

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Without

Certification:

