



ITX E-W60 Silver

The new generation of Mini-ITX from Inter-Tech - modern, stylish and practical. The **E-W60 Silver** is completely made of aluminum and has therefore, also by the many ventilation holes, an excellent thermal load of the components. It also has a very simple and timeless look.

The serial USB connectors, 1x USB 2.0 and 1x **USB 3.0**, are on the side of the case and offer the option to connect external data mediums, like USB sticks. The solid aluminum body reduces annoying vibrations to a minimum. Due to its modest HDD- & Power-LED in the bottom it's a real eye catcher.

Mini-ITX systems are very energy-saving, so that the external 60W Power Supply is sufficient to build up a powerful ITX system. Once it may be a little more power, you can also use an optional 120W Power Supply, since the internal circuit board is able to process an input power of up to 120W.

An intelligent interior layout allows, despite the small space, an easy installation of all components.

Specifications

Motherboard	ITX
Drive Bays	3.5" internal: 1/0* 2.5" internal: 0/2*
Front Connectors	USB 3.0: 1 USB 2.0: 1 Mikrophone: - Speaker: -
Case Openings	WLAN antenna: 2
Cooling System	HDD-Tray: 2x 50x50x10mm or 2x 60x60x10mm (laterally, optional)
Power Input	For 12V plugs with dimensions of 5.5x2.5x10.7mm
Packing Units	Shipping Unit: 1 Piece Packing Unit: 8 Pieces
Guarantee and Warranty	Case 24 Months Warranty Power Supply 24 Months Guarantee
Article Number	88881182
EAN-Code	4260133125544
Scope of Delivery	External 60W Power Supply Circuit board max. 120W Cable ties Screw Set Rubber feet (screwed) Manual
Features	External 60W Power Supply HDD- & Power-LED in the bottom
Accessories	VESA – Bracket (88885241) External 90W PSU (88882098) External 120W PSU (88882103)

*by using 1x 3.5" no 2.5" HDD's mountable

Dimensions and Weight

	Cage	Case	Package
Height	60mm	68mm	272mm
Width	200mm	200mm	130mm
Depth	225mm	225mm	256mm

Weight (net): 1.21Kgs
Weight (gross): 1.86Kgs

DC/DC-Platine:

Connectors	Quantity	Max. Length
Mainboard 20+4Pin	1x	-
P4 12V 4Pin	1x	-
IDE 4Pin	1x	-
S-ATA	2x	-

DC Output	Max. Output Current
+3.30 V	10.0 A
+5.00 V	10.0 A
+5.00 VSB	2.0 A
+12.00 V	4.5 A
-12.00 V	0.15 A

Certification:

