

DYNATRON CORPORATION

NEW PRODUCT SPEC SHEET

Part Number: P785

- For Intel Socket 775 Core 2 Extreme X6800, Core 2 Duo E6000 Sequence, Pentium D 800 Sequence, Pentium 4 and Xeon 3000 Sequence.
- Active cooler for 2U Server & Up.
- Aluminum Radial Fin Heatsink with Copper Core Inserted
- · RoHS compliant.

Overall Specification:

• Dimension: 110.6mm x 110.6mm x 61.8mm

• Weight: 470g ± 5g

Material: Aluminum fin with Copper Core inserted

Screw-on retention

• Backplate includeded.

Thermal Resistance: 0.240 C/W

Fan Specification:

Dimension: 77.0mm x 77.0mm x 20.0mm

Rated Speed:

At Duty Cycle 0%: 1000± 10%RPM
At Duty Cycle 20%: 1000± 10%RPM
At Duty Cycle 100%: 5500± 10%RPM

Bearing: 2X BallRated Voltage: 12V

Power:

At Duty Cycle 0%: 0.54WAt Duty Cycle 20%: 0.54WAt Duty Cycle 100%: 9W



• Maximum Airflow:

o At Duty Cycle 0%: 8.36 cfm

o At Duty Cycle 20%: 8.36 cfm

o At Duty Cycle 100%: 53.90 cfm

Acoustical Noise:

o At Duty Cycle 0%: 20.6 dBA

o At Duty Cycle 20%: 20.6 dBA

o At Duty Cycle 100%: 51.4dBA

0

• Lead Wire Pin Out:

- o Pin#1-Black(-)
- o Pin#2- Yellow(+)
- Pin#3- Green(Tachometer/ Signal Output)
- o Pin#4- Blue (PWM)