



IPC 2U-2308L

The **IPC 2U-2308L** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 2U-2308L** offers the possibility to install eight 2.5" or 3.5" Hot-Swap HDDs, one Slim DVD external and two internal 2.5" HDDs. The **IPC 2U-2308L** has four 80mm fans, that are mounted directly at the back of the drive brackets and ensure therefore a reliable and optimal cooling. Furthermore, the **IPC 2U-2308L** offers the possibility to replace the back of the case with a Low-Profile back*, to facilitate the use of low-profile cards.

***Low-Profile back optional (Art. 88887053)**

Specifications

Motherboard	Mini ITX, µATX, ATX, eATX, SSI EEB maximal motherboard size WxD: 305mm x 345mm, 12" x 13.5"
Drive Bays	2.5" or 3.5" external Hot Swap (max. 6G): 8 5.25" external: 0 Slim DVD external: 1 2.5" internal: 2 3.5" internal: 0
Front connectors	USB 2.0: 2
Cooling System	Internal: 4x 80mm (included, Molex connector)
Controls	Power-Button Rest-Button
LED	Power HDD Activity 3x Network Activity Alert
Power Supply	2U Server Power Supply
Material	1.0-1.2mm Steel
Packing Units	Shipping Units: 1 piece Pallet: 23 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887041
EAN-Code	4260133124608
Scope of Delivery	Screw Set Assembly tool Angle brackets
Features	4x 80mm fan included Drive brackets removable 3 Reusable slot brackets (Riser Card) USB 2.0 as block connector S-ATA/SAS Hot-Swap backplane with SFF-8087 socket ¹

¹ The backplane is only compatible with a SAS-Controller with SFF-8087 connector.
To use the backplane with a SATA-Controller, please order the optional SFF8087 cross-over cables in right quantity.

Dimensions and Weight

	Cage	Case	Package
Height	89mm	89mm	165mm
Width	433mm	480mm	560mm
Depth	650mm	680mm	830mm

Weight (net): 10.14 kg
Weight (gross): 12.4 kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Without

Certification:

