



## **IPC 3U-3316L**

The **IPC 3U-3316L** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 3U-3316L** offers the possibility to install sixteen 2.5" or 3.5" Hot-Swap HDDs, one Slim DVD external and two internal 2.5" HDDs. The **IPC 3U-3316L** has six fans included, from which four 80mm fans are mounted directly at the back of the drive brackets. Another two 60mm fans are mounted at the back and ensure a reliable and optimal cooling.

## Specifications

Motherboard	Mini ITX, µATX, ATX, eATX, SSI EEB maximal motherboard WxD: 305mm x 345mm, 12" x 13.5"
Drive Bays	2.5" or 3.5" external Hot-Swap (max. 6G): 16 5.25" external: 0 Slim DVD external: 1 3.5" internal: 0 2.5" internal: 2
Front connectors	USB 2.0: 2
Cooling System	Internal: 4x 80mm (included, Molex connector) Rear: 2x 60mm (included, 3pin connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity Alert
Power Supply	2HU, 3HU Server Power Supply
Material	1.0-1.2mm Steel
Packaging Units	Shipping Unit: 1 piece Pallet: 15 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887043
EAN-Code	4260133124622
Scope of Delivery	Screw Set Adapter for 2HU redundant PSU Adapter for 2HU PSU Angel bracket for diverse PSU Assembly tool 4x 80mm & 2x 60mm fan included Drive brackets removable USB 2.0 as block connector S-ATA/SAS Hot-Swap backplane with SFF-8087 socket <sup>1</sup>
Merkmale	

<sup>1</sup> The backplane is only compatible with a SAS-Controller with SFF-8087 connector.  
In operation with SATA-Controllers, please order the optional SFF8087 cross-over cables (Art.-No.: 88885237) in right quantity.

## Dimensions and Weight

	Cage	Case	Package
Height	133mm	134mm	195mm
Width	433mm	480mm	560mm
Depth	650mm	685mm	830mm

Weight (net): 13.76 kg  
Weight (gross): 16.20 kg

## Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

**Without**

Certification:

