



Side panel opened



Front panel opened

ITX-E3002

The new generation of Mini-ITX from Inter-Tech - modern, stylish and practical. The E3002 is best known for its space-saving dimensions, but still offers advantages over systems based on ATX standard.

Mini-ITX systems are very energy-saving, so that the external 60W Power Supply is sufficient to build up a powerful ITX system.

Once it may be a little more power, you can also use an optional 120W Power Supply, since the internal circuit board is able to process an input voltage of up to 120W.

An intelligent interior layout allows, despite the small space, an easy installation of all components. Front connectors like 2x USB 2.0 and HD-Audio round out the features.

Specifications

Motherboard	ITX
Drive Bays	3.5" internal: 1/0* 2.5" internal: 0/1*
Front Connectors	USB 2.0: 2
Cooling System	Side: 1x 40mm
Power Input	For 12V plugs with dimensions of 5.5x2.5x10.7mm
Packing Units	Shipping Unit: 1 Piece Packing Unit: 8 Pieces
Guarantee and Warranty	Case 24 Months Warranty Power Supply 24 Months Guarantee
Article Number	88881144
EAN-Code	4260133124738
Scope of Delivery	External 60W Power Supply Circuit board max. 120W S-ATA data cable Cable ties Screw Set Stand Rubber feet (adhesive)
Features	External 60W Power Supply USB 2.0 connector internal as block connector
Optional Accessories	VESA Bracket (Art. 88885230) External 90W PSU (Art. 88882098) External 120W PSU (Art. 88882103)

*HDD mounting rail adjustable, in use of a 2.5" hard drive, you will lose one 3.5" hard drive

Dimensions and Weight

	Cage	Case	Package
Height	60mm	60mm	270mm
Width	190mm	190mm	255mm
Depth	192mm	215mm	130mm

Weight (net): 0.98Kg
Weight (gross): 1.68Kg

DC/DC-Platine:

Connectors	Quantity	Max. Length
Mainboard 20+4Pin	1x	-
P4 12V 4Pin	1x	-
IDE 4Pin	1x	-
S-ATA	1x	-
Floppy	1x	-

DC Output	Output Voltage (V)	Max. Output Current (A)
+3.30 V	+3.30	10.0
+5.00 V	+5.00	10.0
+5.00 VSB	+5.00	2.0
+12.00 V	+12.00	4.5
-12.00 V	-12.00	0.15

Certification:

