



IPC 2U-2129L

The **IPC 2U-2129L** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

For example the **IPC 2U-2129L** provides the possibility to mount a 2U server power supply in the rear of the cage or as an economic alternative a normal ATX power supply* in the front. So if you want to operate this case with a server power supply you just have to exchange the rear HDD-cage with the ATX power supply bracket and remove the rear fan bracket.

Additionally the **IPC 2U-2129L** is equipped with a standard 80mm fan, block connectors for the front fans, perforated slot brackets and dust filters in the front. This guarantees an optimal cooling of the assembled components.

*Through the installation option for standard ATX power supplies, the case provides 6mm more height than a standard 2U case.

Specifications

Motherboard	Mini ITX, mATX, µATX, ATX, eATX, SSI EEB maximal motherboard size WxD: 305mm x 350mm, 12" x 13.8"
Drive Bays	5.25" external: 2 3.5" external: 0 3.5" internal: 6
Front Connectors	USB 2.0: 2
Cooling System	Inter: 4x 80mm (optional, assembled board 4x 3Pin to 1x Molex) Rear: 1x 80mm (included, Molex connector, cannot be used if 2U power supply is mounted)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 2x Network Activity
Power Supply	2U Server PSU ATX PSU*
Material	1.0-1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 18 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887028
EAN-Code	4260133123403
Scope of Delivery	Screw Set Mounting frame for 2HU PSU
Features	Dust filter Possibility to mount a 2U server PSU in the rear or a ATX PSU in the front Standard 1x 80mm rear fan Removable and optional positionable HDD-cages Slot brackets screwed and perforated (rear) 220V internal connection cable for ATX PSU Degradable rack brackets

*Through the installation option for standard ATX power supplies, the case provides 6mm more height than a standard 2U case.

Dimensions and Weight

	Cage	Case	Package
Height	95mm	95mm	175mm
Width	430mm	485mm	560mm
Depth	637mm	670mm	755mm

Weight (net): 7.96Kg
Weight (gross): 9.65Kg

Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Certification:

