No. 100 Oct. 1 Change of the Control of the Control of the Control of Control

CobaNitrox Xtended N-120-G





CobaNitrox Xtended N-120-G

The novel surge baffle system is integrated in the mounting and absorbs emerging vibrations between fan and holder; this means that additional decoupling is no more necessary. Due to this novel surge baffle system the fitting dimensions rest unmodified, in order to permit assembling of every commercial 120mm holder.

Thus this smooth and ball bearing fan, which interacts with the integrated surge baffle system, guarantees minimal running noise.

The fan brackets are installable without screws and can be turned through 180° so that it can be mounted not only to create a pushing airflow but also so to provide a pulling one.



CobaNitrox Xtended N-120-G

Specification

Fan Dimension (H/W/D)	25/120/120mm
Fan Speed	1200U/min
Rated Voltage	12V
Power	0.96W
Air Flow	90cbm/h
Noise Level	19dBA
Connector	3Pin
Package Dimension (H/W/D)	248/160/40mm
Weight (net)	155g
Weight (gross)	215g
Packing Units (VE/VPE)	1/40
Guarantee and Warranty	24 Months Guarantee
Article Number	88885134
EAN-Code	4260133122604
Scope of Delivery	-
Features	Rotatable coloured rubber holder
	Screwless mounting