



## ITX E-i7

The new Mini-ITX generation of Inter-Tech - modern, style-conscious and remarkably practical. The E-i7 is completely made of aluminum and has therefore, also by the many ventilation holes, excellent, thermal load of the components. The massive, black aluminum body also reduces annoying vibrations to a minimum. One USB 2.0 and one **USB 3.0** port at the side of the front and the optional slot-in drive round out the package.

Mini-ITX systems are very energy-saving, so that the external 90W Power Supply is sufficient to build up a powerful ITX system. Once it may be a little more power, you can also use an optional 120W Power Supply, since the internal circuit board is able to process an input voltage of up to 120W.

## Specifications

Motherboard	ITX
Drive Bays	Slot-In: max. 1* 3.5" internal: max. 2* 2.5" internal: max. 2*
Front Connectors	USB 2.0: 1 USB 3.0: 1 Microphone: 1 Headphone: 1
External Connectors	SATA data port: 1 4Pin Molex power connector: 1
Opening rear	WLAN antenna: 2 COM connector: 2
Cooling System	4x 80x80x15mm (laterally, as option)
Packing Units	Shipping Unit: 1 Piece Packing Units: 6 Pieces
Guarantee and Warranty	Case 24 Months Warranty Power Supply 24 Months Guarantee
Article Number	88881175
EAN-Code	4260133125230
Scope of Delivery	External 90W Power Supply DC-board max. 120W Cable ties Screw set Rubber feet (glueable)
Features	External 90W Power Supply 1 low profile PCI card possible

\*1.) in use of only Slot-In, you are able to mount 1x 3.5" or 2x 2.5"  
\*2.) in use of a Slot-In ODD without a PCI card, you are able to mount 2x 3.5" or 2x 2.5"  
\*3.) in use of a Slot-In ODD together with a PCI card, you are able to mount 1x 3.5" or 1x 2.5"  
\*4.) in use of no Slot-In ODD and no PCI card, you are able to mount 2x 3.5" or 2x 2.5"

## Dimensions and Weight

	Cage	Case	Package
Height	100mm	100mm	165mm
Width	245mm	245mm	280mm
Depth	236mm	236mm	285mm

Weight (net): 1.66Kg  
Weight (gross): 2.50Kg

## DC/DC-Platine:

Anschluss	Anzahl	Max. Länge
Mainboard 20+4Pin	1x	-
P4 12V 4Pin	1x	-
IDE 4Pin	1x	-
S-ATA	2x	-

DC Output	Output Voltage (V)	Max. Output Current (A)
+3.30 V	+3.30	10.0
+5.00 V	+5.00	10.0
+5.00 VSB	+5.00	2.0
+12.00 V	+12.00	4.5
-12.00 V	-12.00	0.15

Certification:

