Inter-Tech Elektronik Handels GmbH

Eterno K-six Smart







optional

K-six Smart - The case for innovative users

This sophisticated case with many features such as easily removable drive panels from the front, two easily removable fan mounting brackets with dust filter and a completely continuous hdd cage let the heart of the professional assemblers beat faster.

Besides the diverse & easy mounting the sophisticated cooling concept is a further highlight of the **K-six**. In the lower part of the case the decoupled power supply is receptacle, which provides a vibration-free operation of the power supply. In addition to a standard 120mm fan on the back wall, the **K-six** offers numerous mounting options for additional fans with a maximum size up to 140mm. Two top-mounted and one floor-mounted dust filters ensure clean air circulation inside the case. In addition, the case can be equipped with a water cooling system. The USB 3.0 interface provides a superfast transfer of your data to external media such as USB sticks.



Eterno K-six Smart

Specifications

Motherboard ATX, μATX 5.25" external: 9* Max. Drive Bays

1* 3.5" external: 3.5" internal: 2*

2.5" internal: 5* Anschlüsse Front USB 2.0: 2

USB 3.0: Microphone: Headphone: 1

Cooling System Front: 2x 120mm/1x 120mm

Rear: 1x 92mm or 120mm (1x 120mm included)

Side panel: 2x 120mm or 140mm Top: 2x 120mm or 140mm

Shipping Unit: 1 Piece **Packing Units** Pallet: 20 Pieces

Guarantee and Warranty Case 24 Months Warranty

Article Number 88881190 EAN-Code 4260133126046

1x 120mm fan Scope of Delivery (3Pin connector)

2x 5.25" to 3.5" or 2.5" HDD Adapter

1x 5.25" to 3.5" HDD Adapter with frontpanel

Graphic card holder with rubber pad

Screw set Speaker

Lock loop

Cable ties

Slot bracket Adjustable 5.25" to 3.5"/2.5" HDD Adapter

Removable fan mounting bracket

Exchangeable dust filters in the base and the top

PSU bracket at the bottom (decoupled)

Pilot hole for water cooling system

Intelligent cable management

Stands

Side panels attached with thumbscrews

USB 3.0, USB 2.0 und Audiostecker intern als genormte Blockstecker

HD Audio compatible

*Values can differ in various combinations

Dimensions and Weights

	Cage	Case	Package
Height	430mm	442mm	580mm
Width	195mm	195mm	258mm
Depth	460mm	500mm	490mm
	t): 6.32 Kg oss): 7.36		

ROHS CE **Certification**:

ower Supply	<u> </u>	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4
P8 12V 8Pin	-	_ 4
PCI-Express 6+2Pin	11-0	UĻ
PCI-Express Cain	LNO	W •
IDE 4Pin		-
S-ATA	- .	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Features