



## **IPC 1U-10255**

The **IPC 1U-10255** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 1U-10255** provides the possibility to mount nine 2.5" and one 3.5" internal hard drives. Five standard 40mm fans guarantee an optimal cooling.

Additional extras like easily reachable **USB 3.0** and USB 2.0 connectors and the universal ATX I/O plate complete this total package.

## Specifications

Motherboard	Mini ITX, mATX, µATX, ATX, SSI CEB maximal motherboard size WxD: 305mm x 270mm, 12" x 10.6"
Drive Bays	5.25" external: 2* 3.5" internal: 3* 2.5" internal: 9*
Front Connectors	USB 3.0: 1 USB 2.0: 1
Cooling System	Internal: 5x 40mm (5x included, Molex connector and hot pluggable)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity Alert
Power Supply	1HU Server PSU, FLEX-ATX
Material	1.0/1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 27 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887101
EAN-Code	4260133126220
Scope of Delivery	Screw Set Mounting bracket for FLEX-ATX PSU
Features	5x 40mm fan included USB 3.0 and USB 2.0 as block connector Universal ATX I/O plate 1x Riser slot mounting direction

\*can vary by using several mounting options

## Dimensions and Weight

	Cage	Case	Package
Height	44.5mm	44.5mm	110mm
Width	433mm	480mm	555mm
Depth	550mm	585mm	730mm

Weight (net): 6.90Kg  
Weight (gross): 8.91g

## Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Certification:

