



The **KVM AS-3116DU** is a professional 16-Port KVM-Switch. The **KVM AS-3116DU** is usually used in server racks to switch and manage several installed servers with just one mouse, keyboard and monitor.

The in-build password protection prevent unauthorized access.

The KVM is connected to your computers with the 16 included cables by USB or PS2 and VGA.

Specifications

Keyboard / Mouse Connection	USB/PS2
Monitor Connection	DB15 VGA
Slot for IP-Expansion modul	1
Outputs	16
Maximal manageable PCs	256 max. 2 levels
Suitable for Server Racks	Min. 400mm depth
Connectors	16x DB15 (VGA/USB, Keyboard, Mouse)
LEDs	16x connect, 16x selection
Supported operating system	No Restrictions
Switch Modi	Hotkey
	OSD Menu
Switch Scan-Time	1-255s (OSD chooseable)
DDC	•
Display Resolution	1920x1080
Display Frequency	75Hz
Power	External PSU
Input	9V – 12V, 1A
Material	Rust-resistant Steel
Operating Temperature	-10°C~60°C
Storage Temperature	-30°C~70°C
Humidity	0-80%
MBTF	Average 120000h
Netto-Dimensions (H/W/D)	43x432x156mm
Package-Dimensions (H/W/D)	150x465x200mm
Weight net.	2,02kgs
Weight gros.	5,78kgs
Packing units	Shipping unit: 1 piece
Guarantee and Warranty	24 Month Warranty
Article number	88887162
EAN-Code	4260133127876
Scope of Delivery	16x cables DB15 to VGA/USB/PS2 (180 cm) 19" Installation angle External PSU (Input: 100V-240V, Output: 9V/1A) User manual on CD (English/German)
Features	16x Hotkeys
	Password protection for Keyboard and Monitor
Optional Equipment	KVM IP-Modul KI-3101 (Art. 88887172)

• = existent
- = nonexistent