



IPC 4U-4408

The **IPC 4U-4408** is the perfect rack for a low-priced storage system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 4U-4408** offers the possibility to mount maximal eight 2.5" or 3.5" Hot-Swap HDDs and one internal 2.5" or 3.5" HDD (by using a 2.5" with 9,5mm height also a 3.5" HDD simultaneously). The **IPC 4U-4408** is equipped with two serial 80mm fans.

Spezifikationen

Motherboard	Mini ITX, µATX, ATX, eATX, SSI EEB max. motherboard size WxD: 305mm x 345mm, 12" x 13.5"
Drive Bays	2.5" or 3.5" Hot-Swap (max. 6G): 8 2.5" or 3.5" internal: 1 ¹
Front Connectors	USB 3.0: 1 USB 2.0: 1
Cooling System	Rear: 2x 80mm (serial, 3Pin with 4Pin connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 3x Network Activity 1x Alert
Power Supply	ATX-/Redundant-PSU
Material	1.0-1.2mm steel
Packing Units	Shipping Unit: 1 Piece Pallet: 14 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887191
EAN-Code	4260133128620
Scope of Delivery	Screw Set Frame for ATX PSUs (fixed) and redundant 4U-PSU Adapter for 2U-PSU + optional 80mm fan bracket Mounting frame for several PSU Mounting tool Serial 2x 80mm fans Removable drive bays USB 3.0 and USB 2.0 internal as block connector Hot-Swap Backplane with SFF-8087 connector (max. 6G) ² Snap-in cap Mesh-Grid-Front with dust filter
Features	

¹simultaneously only if 2.5" drive with max. 9.5 mm height

² The backplane is only compatible with a SAS-Controller with SFF-8087 connector.

To use the backplane with a SATA-Controller, please order the optional SFF8087 cross-over cables (88885237) in right quantity

Dimensions and Weight

	Cage	Case	Package
Height	178mm	178mm	240mm
Width	433mm	480mm	550mm
Depth	480mm	520mm	670mm

Weight (net): 9.06 kg

Weight (gross): 11.32 kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 15Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

