Inter-Tech Elektronik Handels GmbH

FSP500-70RGHBB1

Specifications

Output	500W
Mainboard 24Pin	1x
4Pin/ 4+4Pin/ 8Pin 12V	-/-/2x
PCI-Express 6+2Pin	-
PCI-Express 6Pin	-
IDE 4Pin	2x
S-ATA	4x
Floppy	1x
Fan Monitoring	-
115/230V Input	•/• (auto.)
PFC	Active
Fan Dimensions	2x 50mm
Fan Control	Auto.
Redundant	•
Protection Circuit	OTP, OVP, OCP, SCP
MBTF	Average 100000h
PSU Dimensions (H/W/D)	86/150/190mm
Weight (net)	2,89Kg
Packing Units (VPE/PAL)	1/4
Guarantee and Warranty	6 Months Guarantee
Article Number	88887125
EAN-Code	-
Features	Bicoloured LED status display Acoustic alarm signal when a module power failing or a fan error arose 2x Reset buttons to end the alarm signals 4-PIN TTL-cable to get status information of the PSU via Motherboard
80+ Certificate	80 PLUS GOLD

• = existing
- = non existing

Certification:

Errors excepted. No warranty for the correctness of the information State: 29.08.2016

Connectors



Efficiency

	Full Load (100%)	Typical Load (50%)	Light Load (20%)
115VAC	91,62%	92,25%	89,89%
230VAC	91,62%	92,25%	89,89%

AC Input		100-240V 8-4A 60-50Hz						
DC Output		+3.3V	+5V	+12V1	+12V2	+12V3	+5Vsb	-12V
FSP500-70RGHBB1	Max. Current	20A	20A	16A	16A	16A	3A	0,5A
	Max. Combined Power	130W max.						
		500W						

Errors excepted. No warranty for the correctness of the information State: 29.08.2016