



IPC 1U-1304L

The **IPC 1U-1304L** is the ideal case for a small and cheap server solution. With its excellent quality and finish, Inter-Tech established the basis for a very variable case.

The **IPC 1U-1304L** offers the possibility to install four 2.5" or 3.5" Hot-Swap HDDs, one Slim DVD external and two internal 2.5" HDDs. The **IPC 1U-1304L** has six 40mm fans included, that are mounted directly at the back of the drive brackets and ensure therefore a reliable and optimal cooling.

Additional extras like the reusable and perforated slot brackets or the block connector for the fan connections round off the picture.

Specifications

Motherboard	Mini ITX, µATX, ATX, eATX, SSI EEB
Drive Bays	maximal motherboard size WxD: 305mm x 345mm, 12" x 13.5"
	2.5" or 3.5" Hot-Swap (max. 6G): 4
	5.25" external: 0
	Slim DVD external: 1
	3.5" internal: 0
	2.5" internal: 2
Front connectors	USB 2.0: 2
Cooling System	Internal: 6x 40mm (included, Molex connector)
Controls	Power-Button
LED	Reset-Button
	Power
	HDD Activity
	3x Network Activity
	Alert
Power Supply	1U Server Power Supply
Material	1.0-1.2mm Steel
Packing Unit	Shipping Unit: 1 piece
	Pallet: 29 pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887040
EAN-Code	4260133124592
Scope of Delivery	Screw Set
	Assembly tool
	Mounting bracket
Features	6x 40mm fan included
	Fan connecting possibilities as block
	Drive brackets removable
	Reusable and perforated slot brackets,
	convertible for left or right mounting, screwless
	(rear)
	USB 2.0 as block connector
	S-ATA/SAS Hot-Swap backplane*

*The included backplanes are only for the connection to SATA controller. For the connection to SAS controller please order the optional available Mini

Dimensions and Weight

	Cage	Case	Package
Height	44.5mm	44.5mm	120mm
Width	433mm	480mm	560mm
Depth	650mm	680mm	835mm

Weight (net): 7.7 kg
Weight (gross): 9.8 kg

Power Supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

